

Lubri-Cup™ EM

Automatic single-point lubricator dispenses Chesterton grease to critical areas, eliminating over and under greasing.

Environmentally Friendly

- Lubri-Cup™ EM comes standard with easy to dispose replaceable service pack that includes both grease pouch and battery pack.

User Friendly

- A compact, convenient and sturdy design that is simple to operate and maintain. A large LCD screen allows easy monitoring. The unit can operate at high pressure if required

Equipment Friendly

- Weight balanced design for precise and reliable Lubrication. Replaceable service packs with Chesterton's industrial greases offer extended bearing life and reliability even under the harshest conditions offload, temperature, water and corrosion.

Cost Effective

- If required the Lubri-Cup™ EM can be used for the automatic lubrication of up to 8 points using a progressive divider block.



Microprocessor controlled, "pulse" delivery system

Programmable - Operates up to 12 months

Replaceable service packs

Lubricates up to 8 bearings up to 6 m (19 feet) away

Sealed microprocessor

Specifications	
Fitting	Break-free 3/8" brass
Operating temperature	-15 to 60 °C (5 °F~140 °F) <i>Lithium ion battery available for temperatures down to -40° C (-40° F)</i>
Typical Pressure	20bar (280psi)
Maximum Pressure	80bar (1,160psi)
Voltage	DC 4.5V (replaceable battery pack)
Grease Volume	250CC

Order Numbers	
Lubri-Cup EM	084307
615 #1 M Service Pack	084313
615 #2 M Service Pack	084314
625 M Service Pack	084315
630 M Service Pack	084312
633 M Service Pack	084316
635 M Service Pack	084317