

# Technical Data for Mechanical Packing



## D5F 5A 9HF MH97 < B=7NB9

Material: 316 Stainless Steel

Temperature: -200 to 500 °F

Pressure: 0 to 1000 PSI

Speed: 0 to 1000 RPM

Application: General Purpose

Lead Time: 4-6 Weeks

Weight: 1.5 lbs per foot

Dimensions: 3/16" x 1/4" x 1/4" (OD x ID x Thickness)

Size	Weight (lb/ft)	OD (in)	ID (in)	AWC
3/16	4,7	2	0,908	175910
1/4	6,4	2	0,908	175911
		5	2,270	175912
5/16	8,0	2	0,908	175913
		5	2,270	175914
3/8	9,5	2	0,908	175915
		5	2,270	175916
		10	4,540	175917
-	10,0	2	0,908	175918
		5	2,270	175919
7/16	11,1	2	0,908	175920
		5	2,270	175921
-	12,0	2	0,908	175922
		5	2,270	175923
		10	4,540	175924
1/2	12,7	2	0,908	175924
		5	2,270	175925
9/16	14,3	10	4,540	175926
		5	2,270	175927
		10	4,540	175928
5/8	15,9	10	4,540	175929
11/16	17,5	10	4,540	175930
3/4	19,1	10	4,540	175931
-	20,0	10	4,540	175932
13/16	20,6	TO ORDER		
7/8	22,2	10	4,540	175933
15/16	23,8	10	4,540	175934
1	25,4	10	4,540	175935

General Purpose Mechanical Packing, 316 Stainless Steel, 3/16" x 1/4" x 1/4" (OD x ID x Thickness)

Material: 316 Stainless Steel, Temperature: -200 to 500 °F, Pressure: 0 to 1000 PSI

Speed: 0 to 1000 RPM, Application: General Purpose, Lead Time: 4-6 Weeks

Weight: 1.5 lbs per foot, Dimensions: 3/16" x 1/4" x 1/4" (OD x ID x Thickness)

Material: 316 Stainless Steel, Temperature: -200 to 500 °F

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties expressed, or implied, including warranties of merchantability and fitness for a particular purpose or use. Liability, if any is limited to product replacement only.

Technical data reflects results of laboratory tests and is intended to indicate general characteristics only. A.W. Chesterton Company disclaims all warranties expressed, or implied, including warranties of merchantability and fitness for a particular purpose or use. Liability, if any is limited to product replacement only.

DISTRIBUTED BY: